



Technical Data		
Material	Anodized Aluminum (UT-PBA) Stainless Steel (UT-PBS)	
Contact Materials	Aluminum, Brass, Buna NBR	
Seal	Buna N	
Function	5/2	
Assembly & Connection	24 x 32 Namur	
Flow Coefficient	Spring Stroke $C_v = 0.80$	Pressure Stroke $C_v = 1.20$

NOTES

- PART NUMBER IS UT-PBS-1SR IF MADE FROM STAINLESS STEEL
- PART NUMBER IS UT-PBA-1SR IF MADE FROM ALUMINUM

DESCRIPTION		NOTICE: THIS DRAWING INCLUDES THE DESIGN AND PRINCIPLES DISCLOSED AND IS THE SOLE PROPERTY OF UNITORQ AND ITS AFFILIATES. IT SUBMITTED WITH THE UNDERSTANDING THAT IT IS NOT TO BE REPRODUCED, NOR COPIED IN WHOLE OR IN PART, NOR LOANED OR OTHERWISE COMMUNICATED TO ANY THIRD PARTY, NOR USED IN ANY MANNER DETRIMENTAL TO THE INTERESTS OF UNITORQ OR ANY OF ITS AFFILIATES WITHOUT THE EXPRESSED WRITTEN CONSENT OF UNITORQ. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.				<p>2150 Boggs Road, Suite 410 DULUTH, GEORGIA U.S.A. 30096 Ph: 770-446-7074 Fax: 770-447-1825 www.unitorq.com</p> 		ISO 9001 - 2008 EDITION					
PRODUCT:	Purge Block	PART NUMBER:	See Note	SALES DRAWING NUMBER:	PurgeBlock1S	DWN BY:	MBRo	DATE:	02/23/2022	SCALE:	1:1	REV.	1